



DEHN (U.K.) LTD

Tel. 01484-859 111

Fax 01484-859 222

info@dehn.co.uk



Dimension drawing DSP 2 P 415/ DSP 2 PA 415 in mm

Available from

DSP 2 P 415 (Part No. 902 660) and DSP 2 PA 415 (Part No. 902 661): Mains connection box set for 3-phase 240/415 V TN-(C-)S systems, with IP 65 enclosure premounted with DEHNguard modular surge arrester (Part No. 952 400); Type DSP 2 PA 415 (Part No. 902 661) premounted with surge arresters (Part No. 952 405) with integrated remote signalling contact for monitoring system

- Ready-to-install equipment for use acc. to the lightning protection zones concept as required in BSEN 62305-4
- Premounted with DEHNguard M ... surge arrester
- Quick and easy installation as premounted with SPD arrangements
- Maximum discharge capacity (I_{max} 40 kA) due to powerful zinc oxide varistors
- High reliability due to "Thermo Dynamic Control" monitoring device
- Allows for easy replacing of protection modules due to module releasing button
- Operating state/fault indication by mark in the inspection window (and remote signalling contact - for type DSP PA 415 only)
- Enclosure with transparent cover, degree of protection: IP 65

DSP 2 P 415	
SPD Features	:
SPD according to EN 61643-11	Type 2
SPD according to IEC 61643-1	Class II
Nominal a.c. voltage [U_N]	240 / 415 V
Power supply system	TN-(C-)S system
Max. continuous operating a.c. voltage [U_C]	275 V
Nominal discharge current (8/20 μs) [I_n]	20 kA
Max. discharge current (8/20 μs) [I_{max}]	40 kA
Voltage protection level [U_p]	≤ 1.25 kV
Voltage protection level for 5 kA [U_p]	≤ 1 kV
Response time [t_A]	≤ 25 ns
Max. mains-side overcurrent protection	125 A gL/gG
Short circuit withstand capability for max. mains-side overcurrent protection	50 kA _{rms}
Temporary overvoltage (TOV) [U_{TOV}]	335 V / 5 sec.
TOV characteristics	withstand
Operating state/Fault indication	green / red
Cross-sectional area (min.)	1.5 mm ² solid/flexible
Cross-sectional area (max.)	35 mm ² stranded/25 mm ² flexible
SPD material	red thermoplastic, UL 94 V-0
MAINS CONNECTION BOX Features	:
Ambient temperature range [T_U]	-25°C...+40°C
Enclosure material	polystyrene

Impact strength according to DIN EN 50102	IK 07 (2 Joule loads)
Degree of protection acc. to EN 60529	IP 65
Cover type	transparent cover
Colour of enclosure	grey
Number of cable entries	4 elastic cable entry
Capacity	5 mods.
Dimension (W x H x D)	125 x 200 x 122 mm
Ordering information	
Type	DSP 2 P 415
Part No.	902 660
Packing unit	1 pcs.

Change in form and technology, with masses, weights and materials we reserve ourselves in the sense of the progress of the technology. The illustrations are noncommittal.